


1		2		3		4		5		6	
Document No. QR4-700-T-003				REV.		DESCRIPTION		REVISOR		DATE	
REV. A/0				0				YQ.XIE		07.28.2015	
										APPROVED David	



SPECIFICATIONS	
Part's Number	JIWR75-12D7-14K25T14K75
Frequency(GHz)	14.25~14.75
Direction	-
Insertion Loss(dB)MAX	0.30
Isolation(dB)MIN	20.0
Return Loss(dB)MIN	20.0
3rd IMD(dBc)MAX	-
Power FWD/REV/PK(Watt)	15/5/-
Operating Temperature(°C)	-40~+85
Storage Temperature(°C)	-
2nd/3rd Harmonic(dBc)	-
Termination/Attenuator(Watt/dB)	-
Tab(W×LG×THK)(mm[Inch])	-
Additional Notes	-

JQL JQL Electronic Inc				
MATERIAL: AL		DWG NO: JIWR75-12D7-14K25T14K75		
SURFACE TREATMENT:		DWG BY:	YQ.XIE	07.28.2015
DESCRIPTION: WAVEGUIDE ISOLATOR		CHK'D BY:		SCALE
		APPV'D BY:		1:1
		Unit: mm[inch]	Tolerance: Liner: ±0.25 Anguar: ±0.5°	The First:
				A4



This document is the property of JQL Electronic Inc. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Electronic Inc.