


1		2		3		4		5		6			
Document No.	QR4-700-T-003	REV.	A/0	REV.	0	DESCRIPTION		REVISOR	ywzhang	DATE	05.26.2014	APPROVED	David



ITEM	SPECIFICATIONS	
Passband(MHz)	CH1:698-793	CH2:824-894
Insertion Loss(dB)	0.6 max	
Passband Ripple(dB)	0.4 max	
Return Loss(dB)	18 min	
Isolation(dB)	50 min	
Power Handling(W)	100 avg	
Impedance(Ω)	50	
Temperature(°C)	-25 to +55	
Connector	N-Female	
Notes		

JQL JQL Electronic Inc 3501 Algonquin Road, Ste 230 1(888) 236-9828
Rolling Meadows, IL 60008 (630) 823-2902

MATERIAL:	DWG NO: JFCD0698T0894NF			
SURFACE TREATMENT: PAINTED BLACK	DWG BY:	ywzhang	05.26.2014	SACLE
	CHK'D BY:			
DESCRIPTION: DIPLEXER	APPV'D BY:			1:3
	Unit:	Tolerance:	The First:	A4
	mm[inch]	Liner: ±0.25 Anguar: ±0.5°		



This document is the property of JQL Electronic Inc. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Electronic Inc.