



REV.	DESCRIPTION	REVISOR	DATE	APPROVE

**SPECIFICATIONS**

P/N: JIWR75-25-TBD  
 FREQ: 10.00~16.00GHz  
 Bandwidth Up To 30%  
  
 ISOLATION: 23dB MIN  
 INS LOSS: 0.25dB MAX  
 VSWR: 1.20:1 MAX  
 PWR FWD/REV 10W/5W  
 WAVEGUIDE: WR75  
 TEMP: -30~+70C

This document is the property of JQL Electronic Inc. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Electronic Inc.

<b>JQL JQL Electronic Inc</b>		500 Lake Cook Road, Suite 350 Deerfield, IL 60015, USA		Tel : 1(888)236-9828 Fax: 1(630)823-2902	
MATERIAL: <b>ALUMINUM</b>		DWG NO.  <b>JIWR75-25-TBD</b>			
SURFACE TREATMENT:					
DESCRIPTION: <b>WAVEGUIDE</b>		NAME		DATE	
		SY		01.13.09	
		GC		01.13.09	
		JZ		01.13.09	
		TOLERANCE		Q.A	
		Liner: ±0.1mm			
		Angular: ±0.5°			
				REV:	
				0	
				A4	