



1	2
Document No.	QR4-700-T-003
REV.	A/0

4	5	6		
REV.	DESCRIPTION	REVISOR	DATE	APPROVED
0		JUNMA	07.13.2017	David



SPECIFICATIONS	
Part's Number	JCC0450T0480N20
Frequency(GHz)	0.450~0.480
Direction	-
Insertion Loss(dB)MAX	0.25
Isolation(dB)MIN	50.0
Return Loss(dB)MIN	50.0
3rd IMD(dBc)MAX	-
Power FWD/REV/PK(Watt)	200/200/-
Operating Temperature(°C)	-20~+75
Storage Temperature(°C)	-
2nd/3rd Harmonic(dBc)	-
Termination/Attenuator(Watt/dB)	-
Tab(W×LG×THK)(mm[Inch])	-
Additional Notes	-



This document is the property of JQL Electronic Inc. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Electronic Inc.

JQL JQL Electronic Inc				
MATERIAL: STEEL		DWG NO: JCC0450T0480N20		
SURFACE TREATMENT: NICKEL PLATING		DWG BY:	JUNMA	07.13.2017
DESCRIPTION: COAXIAL CIRCULATOR		CHK'D BY:		SCALE
		APP'V'D BY:		1:2
Unit: mm[inch]		Tolerance: Liner: ±0.25 Anguar: ±0.5°	The First: 	
				A4