



1	2
Document No.	QR4-700-T-003
REV.	A/0

4	5	6		
REV.	DESCRIPTION	REVISOR	DATE	APPROVED
0		ZC.Wu	10.13.2014	David



SPECIFICATIONS	
Part's Number	JCC2300T2500NMNFNF10
Frequency(GHz)	2.300~2.500
Direction	-
Insertion Loss(dB)MAX	0.35
Isolation(dB)MIN	20.0
Return Loss(dB)MIN	20.0
3rd IMD(dBc)MAX	-
Power FWD/REV/PK(Watt)	100/100/-
Operating Temperature(°C)	-35~+70
Storage Temperature(°C)	
2nd/3rd Harmonic(dBc)	-
Termination/Attenuator(Watt/dB)	-
Tab(W×LG×THK)(mm[Inch])	-
Additional Notes	-



This document is the property of JQL Electronic Inc. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Electronic Inc.

<b>JQL</b> JQL Electronic Inc	
<b>MATERIAL:</b> STEEL	<b>DWG NO:</b> JCC2300T2500NMNFNF10
<b>SURFACE TREATMENT:</b> NICKEL PLATING	DWG BY: ZC.Wu 10.13.2014 SCALE
<b>DESCRIPTION:</b> COAXIAL CIRCULATOR	CHK'D BY: APPV'D BY: 1:1
Unit: mm[inch]	Tolerance: Liner: ±0.25 Anguar: ±0.5° The First:
	A4