




1	2
Document No.	QR4-700-T-003
REV.	A/0

3	4	5	6	
REV.	DESCRIPTION	REVISOR	DATE	APPROVED
0		LJ.Zhang	08.02.2013	David



SPECIFICATIONS	
Part's Number	JIC0791T0821N1
Frequency(GHz)	0.791~0.821
Direction	-
Insertion Loss(dB)MAX	0.35
Isolation(dB)MIN	20.0
Return Loss(dB)MIN	20.0
3rd IMD(dBc)MAX	-75 with +43 dBm/tone
Power FWD/REV/PK(Watt)	10/10/100
Operating Temperature(°C)	+15~+40
Storage Temperature(°C)	-
2nd/3rd Harmonic(dBc)	-
Termination/Attenuator(Watt/dB)	100/-
Tab(W×LG×THK)(mm[Inch])	-
Additional Notes	-

JQL JQL Electronic Inc				
MATERIAL: STEEL		DWG NO: JIC0791T0821N1		
SURFACE TREATMENT: NICKEL PLATING		DWG BY:	LJ.Zhang	08.02.2013
DESCRIPTION: COAX ISOLATOR		CHK'D BY:		SACLE
		APPV'D BY:		2:3
		Unit: mm[inch]	Tolerance: Liner: ±0.25 Anguar: ±0.5°	The First:
				A4



This document is the property of JQL Electronic Inc. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Electronic Inc.