




1	2
Document No.	QR4-700-T-003
REV.	A/0

4	5	6		
REV.	DESCRIPTION	REVISOR	DATE	APPROVED
0		M.Hao	09.17.2013	David



SPECIFICATIONS	
Part's Number	JIC0875T0895S3
Frequency(GHz)	0.875~0.895
Direction	-
Insertion Loss(dB)MAX	0.25
Isolation(dB)MIN	23.0
Return Loss(dB)MIN	21.0
3rd IMD(dBc)MAX	-75@2x50W
Power FWD/REV/PK(Watt)	30/30/300 DUTY:10%,PW:1usec
Operating Temperature(°C)	-20~+80
Storage Temperature(°C)	-20~+85
2nd/3rd Harmonic(dBc)	-
Termination/Attenuator(Watt/dB)	100
Tab(W×LG×THK)(mm[Inch])	-
Additional Notes	-

JQL JQL Electronic Inc				
MATERIAL: STEEL		DWG NO: JIC0875T0895S3		
SURFACE TREATMENT: NICKEL PLATING		DWG BY:	M.Hao	09.17.2013
DESCRIPTION: COAXIAL ISOLATOR		CHK'D BY:		SACLE
		APPV'D BY:		1:1
		Unit:	Tolerance:	The First:
		mm[inch]	Liner: ±0.25	
			Anguar: ±0.5°	A4



This document is the property of JQL Electronic Inc. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Electronic Inc.