




1		2		3		4		5		6			
Document No.	QR4-700-T-003	REV.	A/0	REV.	0	DESCRIPTION		REVISOR	LJ.Zhang	DATE	08.23.2013	APPROVED	David



SPECIFICATIONS	
Part's Number	JIC19K2T21K2SMSF1
Frequency(GHz)	19.20~21.20
Direction	-
Insertion Loss(dB)MAX	0.50
Isolation(dB)MIN	18.0
Return Loss(dB)MIN	23.0
3rd IMD(dBc)MAX	-
Power FWD/REV/PK(Watt)	1/1/-
Operating Temperature(°C)	-40~+85
Storage Temperature(°C)	-
2nd/3rd Harmonic(dBc)	-
Termination/Attenuator(Watt/dB)	1
Tab(W×LG×THK)(mm[Inch])	-
Additional Notes	-



This document is the property of JQL Electronic Inc. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Electronic Inc.

JQL JQL Electronic Inc	
MATERIAL: STEEL	DWG NO: JIC19K2T21K2SMSF1
SURFACE TREATMENT: NICKEL PLATING	DWG BY: LJ.Zhang 08.23.2013 SACLE
	CHK'D BY:
DESCRIPTION: COAX ISOLATOR	APPV'D BY:
	Unit: mm[inch] Tolerance: Liner: ±0.25 Anguar: ±0.5°
	The First: 3:2 A4