Document No.	QR4-700-T-003
REV.	A/0

REV.	DESCRIPTION	REVISOR	DATE	APPROVED
SK0		J.Z	02.24.2022	HC.Qiu







SPECIFICATIONS	
Part's Number	JCC1400T1900SMSFSF6
Frequency(GHz)	1.400~1.900
Direction	-
Insertion Loss(dB)MAX	0.5
Isolation(dB)MIN	18.0
Return Loss(dB)MIN	18.0
3rd IMD(dBc)MAX	-
Power FWD/REV/PK(Watt)	60/60/-
Operating Temperature(°C)	-30~+75
Storage Temperature(°C)	-
2nd/3rd Harmonic(dBc)	-
Termination/Attenuator(Watt/dB)	-
Tab(W×LG×THK)(mm[Inch])	-
Additional Notes	-

JQL Technologies Corporation.

MATERIAL: STEEL

SURFACE TREATMENT: NICKEL PLATING OR SILVER PLATING

DESCRIPTION: COAXIAL CIRCULATOR

DWG NO: JCC1400T1900SMSFSF6

DWG BY:	J.Z	02.24.2022	SCALE
CHK'D BY:			1:1
APPV'D BY:			
Unit: mm[inch]	Tolerance: Liner: ±0.25 Anguar: ±0.5°	The First:	A4

RoHS COMPLIANCE

This document is the property of JQL Technologies Corporation. It cannot be copied, duplicated, used for manufacturing purposes or communicated to third party as a whole or partly, without the written consent of JQL Technologies Corporation.

WEIGHT:

SHEET 1 OF 1